

Retrofit Shower Floors

SWANSTONE SHOWER FLOORS

With Fit-Flo™ Drain

and commercial surfaces.

Manufactured from Swanstone solid surface

(See page 2 for detailed information.)

Recommended for high-use traffic areas

WARRANTY
Limited Lifetime – Residential
Limited 10-year – Commercial


FEATURES

• Reinforced solid surface means color and texture. run all the way through and cannot wear away.

- Will not mold or mildew, no grout to clean.
- Coordinates with Swanstone shower and bath systems.
- Pebbled, slip-resistant surface.
- Without expensive plumbing re-work, this floor can be installed in the same area once occupied by a standard bathtub.

	Nominal	Rough-In Dimensions					
Model	Size	60"	32"	8"	15"		
SR-3260L	32" x 60"	60-3/8"	32-3/16"	8-3/16"	15-3/16"		
(Left-side dr	ain)						
SR-3260R	32" x 60"	60-3/8"	32-3/16"	8-3/16"	15-3/16"		
(Right-side drain)							

IMPORTANT: Rough-in dimensions are provided for reference only. You must measure the actual shower floor and check local building code requirements before construction of the stud wall.



Retrofit Shower Floor left side drain 3" dia. Retrofit Shower Floor right side drain 3" dia. 3" dia. 3" dia.

SPECIFICATIONS

Retrofit Shower Floors With Fit-FloTM Drain

Model	Part	Nominal Size Dimensions	•		Carton Dims. In.	Cu. Ft.
SR-3260L	SRo326oLM	32" D x 60" W (Retrofit left drain)	59	_	66 x 37 x 10	15
SR-3260R	SRo3260RM	32" D x 60" W (Retrofit right drain) 59	-	66 x 37 x 10	15

Includes: One code-approved compression-molded Swanstone floor with molded-in Fit-Flo drain.

Packaging: Each floor packed in a rectangular carton.

COLORS

←8"→

(See inside back cover for color sample.)

Solid Colors:

- White (010)
- Bone (037)
- Bisque (o18)Bright White (137)
- Pearl (138)

Aggregate Colors:

- Acorn (123) 💋
- Almond Galaxy (046)
- Arctic Granite (035)
- Baby's Breath (168)
- Barley (091)
- Bermuda Sand (040)
- Canyon (124) 💋
- Caraway Seed (169)
- Cloud Bone (126)
- Cloud White (125)
- Cornflower (063)
- Glacier (121) 💋

- Golden Steppe (128)
- Gray Granite (042)
- Ice (130)
- Indian Grass (071)
- Mountain Haze (129)
- Night Sky (012)
- Pebble (072)
- Prairie (122) 💋
- Sierra (094)
- Tahiti Desert (050)
- Tahiti Gray (053)
- Tahiti Ivory (059)
- Tahiti Matrix (058)
- Tahiti Sand (051)
- Tahiti Terra (055)
- Tahiti White (011)
- Tundra (131)
- Winter Wheat (o6o)

STANDARDS AND RATINGS

American National Standard Institute—ANSI Z124.1.2 International Association of Plumbing and Mechanical Officials (IAPMO)—Listed CSA Standard B45.5 by IAPMO Uniform Plumbing Code (UPC)

For a complete list of tests and results see the Technical Data Sheet.

SUPPORT DOCUMENTS

Installation instructions available at swanstone.com.



MAINTENANCE AND CLEANING INFORMATION

Clean regularly with common household liquid cleaners and a sponge or soft cloth. For hard water stains, scale removers can be used. If necessary, abrasive cleaners can be used with a nylon brush or pad to remove build up on the shower floor surface. **Do not** use a metal-scouring pad or a wire brush, as it will damage the surface. **Do not** use "leave on" cleaning products, such as automatic spray shower cleaners. Prolonged contact with harsh chemicals could have an adverse reaction over time and discolor surfaces. **Do not** use cleaning agents that caution use on acrylic, polyester or plastics.